

PRODUCT PROFILE

ROLL-ON



TUFF SYSTEM ADVANTAGE

Roll-On helps decrease installation and production times, improving efficiency, while eliminating the use of other harmful solvent based adhesives. Tuff membranes must be placed onto fresh wet adhesive allowing for adhesive transfer to the back of the vinyl. Roll-On can also be heat activated.

For additional information, specifications, CAD drawings or MSDS, please contact Tuff Industries Inc.

Toll Free: 1-877-860-9333

NOTES: This document is not an installation guideline.

Tuff Industries Inc. will not be responsible for the improper use or installation of its products.

FEATURES

- Latex based adhesive
- For use on flat and vertical surfaces
- Fast cure time
- Low odor
- Compatible with all Tuff membranes

TECHNICAL NOTES

- Apply at temperatures at or above 40 °F / 4 °C and rising
- Applied using a Tuff solvent resistant adhesive roller
- Coverage: 160 sq. ft. / gal – 1 sided
- Coverage: 80 sq. ft. / gal – 2 sided
- Do not freeze
- Frozen adhesive must be discarded

PACKAGING

- Single units: 3 US gal / 11.34 L
- Skid – 60 pails – 3 US gal / 11.34 L



TUFF INDUSTRIES
INCORPORATED
WATERPROOFING SOLUTIONS